

Ding Oil International Trading Company Ltd

MATERIAL SAFETY DATA SHEET

BOD Radiator Stop Leak

1. Product & Company Identification

Product Name: **BOD Radiator Stop Leak**
Product Use: Additive
Supplier: Ding Oil International Trading Company Ltd
Address: No.100-61, Fengren Rd., Fengshan Dist.,
Kaohsiung City 830, Taiwan
Tel: +886 7 740 5126 Fax: +886 7 7405127
Email: service.BOD@gmail.com
EMERGENCY TELEPHONE NUMBER: DOMESTIC +886 7 7405126
INTERNATIONAL: +886 7 7405216

2. Composition & Ingredients

Chemical Properties

Ingredients	Concentration (%)	CAS No.	EINECS No.
Deionized water	90.0%	7732-18-5	
Sodium nitrite	5.0%	7632-00-0	
Partial sodium silicate	5.0%	6834-92-0	

3. Hazards Identification

POTENTIAL HEALTH EFFECTS

NON HAZARDOUS SUBSTANCE, NON DANGEROUS PRODUCTS.

Emergency : May cause minor irritation as contact with skin and eyes

Chronic : This product has not been tested as a whole for chronic health effects.

POTENTIAL ENVIRONMENTAL EFFECTS : None applicable

PHYSICAL & CHEMICAL HAZARDS : None applicable

SPECIAL HAZARDS : None applicable

MAJOR SYMPTOMS :

- EYES : Minor irritation
- SKIN CONTACT : No irritation
- SWALLOWING : May cause throat & respiration irritation.

- **INHALATION :** This good is not likely to cause an inhalation hazard at normal temperature, but when breathing the vapor or mist or heat may cause respiration irritation (nose, throat and lung).

4. First Aid Measures

- **BREATHING :** Move the person to fresh air, get medical attention and see a doctor if breathing difficulty occurs.
- **SKIN :** Remove contaminated clothing. Wash skin thoroughly with soap and water. See a doctor if skin irritation persists or pain develops.
- **EYES :** Wash eyes immediately with clean water for at least 15 minutes while holding the eyelid open. See a doctor if irritation persists.
- **INGESTION :** Do not make person vomit and see a doctor immediately.

If vomiting occurs, avoids breathing the substance into respiration (lungs). Never give anything by mouth to an unconscious person.

5. Fire Fighting Measure

FIRE EXTINGUISHING AGENTS : **Foam, carbon dioxide, dry chemical powder**

- **HAZARDOUS COMBUSTION PRODUCTS :**

**Burning at high heat may decompose and produce carbon dioxide, phosphorus oxides, and undefined organic compounds.

- **FIRE FIGHTING INDICATIONS :**

**None.

- **EXPLOSION HAZARDS :**

**Water may cause the hot oil splashing, and oil will float on the water. Gases or vapors can cause burning.

6. Accidental Release Measures

- **INDIVIDUAL NOTES :**

** Immediately stop the leak of the liquid, remove the leaked liquid as soon as possible.

- **ENVIRONMENTAL NOTES :**

** Prevent pollution of water or soil.

- **CLEAN PROCEDURES :**

** Clean up small spill requires appropriate methods, such as use absorbent material to absorb or use motor extract.

7. Handling and Storage

- ◆ **Handling :**

- A. Don't do the container welding, heating or drilling and the lid should be closed. It's dangerous after the empty bucket sufficiently heated.
- B. When do the process of handling, keep the proper temperature and ventilation of the environment.
- C. Avoid with water, or cause the pollution of water.

◆ **Storage :**

- A. Store containers in a cool, dry, ventilated place, and keep them away from flame, sparks or other sources of ignition.
- B. The containers must be safely sealed clearly marked and avoid damage and collision.

8. Exposure Controls / Personal Protection

Engineering controls : There is no need ventilation, but use this item under a high pressure job in general; there is the special ventilation equipment.

Inhalation Protection : Wear respiratory masks.

Hands/Feet Protection: suitable and durable plastic or rubber gloves, wear securely footwear like rubber.

Eye Protection : Wear safety glasses with side shields, chemical goggles.

Skin & Body Protection : Any routine contact with used engine oil should require wearing protective clothing such as gloves, boots or apron made of neoprene, nitrile, etc. suitable for the application.

Hygiene :

- a. Keep good personal. Wash entirely with soap and water after handling product.
- b. Prohibit smoking and eating in working area.
- c. Clean affected clothing shoes, etc.
- d. Keep working areas clean.

9. Physical & Chemical Properties

Appearance & color :	Silver liquid
Boiling point (deg. C) :	98.8 -104.4°C
Vapor pr. (mm Hg@ 20 deg. C) :	None
Density (kg/l at 15 deg. C) :	1.01-1.09 @15°C , g/cm ³
Vapor density (air = 1) :	None
pH :	None
Solubility (water) :	Not available
Volatile Component (% vol.) :	Not determined
Evaporation :	None

16. Other information

Issuer name: Ding Oil International Trading Company Ltd.
No.100-61, Fengren Rd., Fengshan Dist., Kaohsiung City 830, Taiwan
Tel: +886 7 7405126

Issued date: Apr. 20, 2017

Revision No. : 1

Label/other information: Not available.

Remarks to reader:

The information provided in this MSDS is from reliable source we trust. We do not guarantee any liability for consequences of the use this information since it may be used under condition out of our control or knowledge.

And it is also possible, that extra data could be made available after this MSDS was issued. All the material may present unknown hazards, the users should review this information and use with caution. The final determination of the suitability of any material is the sole responsibility of the user.