Ding Oil Technology Trading Company Ltd

MATERIAL SAFETY DATE SHEET

BOD Gasoline Additive

1. Product & Company Identification

Product Name: BOD Gasoline Additive

Product Use: Additive

Supplier: Ding Oil Technology Trading Company Ltd Address: No.100-61, Fengren Rd., Fengshan Dist.,

Kaohsiung City 830, Taiwan

Tel: +886 7 740 5126 Fax: +886 7 7405127

Email: service.BOD@gmail.com

EMERGENCY TELEPHONE NUMBER: DOMESTIC +886 7 7405126

INTERNATIONAL: +886 7 7405216

2. Composition & Ingredients

Chemical Properties: Hydrocarbons

Ingredients	Concentration (%)	CAS No.	EINECS No.
Methanol	70.0%	67-56-1	
Propylene glycol methyl ether	15.0%	107-98-2	
2-butanon <mark>e</mark>	15%	78-93-3	
*			*

3. Hazards Identification

POTENTIAL HEALTH EFFECTS

NON HAZARDOUS SUBSTANCE, NON DANGEROUS PRODUCTS.

Emergency: May cause minor irritation as contact with skin and eyes

Chronic: This product has not been tested as a whole for chronic health effects.

POTENTIAL ENVIRONMENTAL EFFECTS: None applicable

PHYSICAL & CHEMICAL HAZARDS: None applicable

SPECIAL HAZARDS: None applicable

MAJOR SYMPTOMS:

EYES: Minor irritation

SKIN CONTACT: No irritation

- SWALLOWING: May cause throat & respiration irritation.
- > INHALATION: This good is not likely to cause an inhalation hazard at normal temperature, but when breathing the vapor or mist or heat may cause respiration irritation (nose, throat and lung).

4. First Aid Measures

- BREATHING: Move the person to fresh air, get medical attention and see a doctor if breathing difficulty occurs.
- > SKIN: Remove contaminated clothing. Wash skin thoroughly with soap and water. See a doctor if skin irritation persists or pain develops.
- Wash eyes immediately with clean water for at least 15 minutes while holding the eyelid open. See a doctor if irritation persists.
- > INGESTION: Do not make person vomit and see a doctor immediately.

If vomiting occurs, avoids breathing the substance into respiration (lungs). Never give anything by mouth to an unconscious person.

5. Fire Fighting Measure

FIRE EXTINGUISHING AGENTS: Foam, carbon dioxide, dry chemical powder

- HAZARDOUS COMBUSTION PRODUCTS :
- **Burning at high heat may decompose and produce carbon dioxide, phosphorus oxides, and undefined organic compounds.
- FIRE FIGHTING INDICATIONS:
- **None.
- EXPLOSION HAZARDS :
- **Water may cause the hot oil splashing, and oil will float on the water. Gases or vapors can cause burning.

6. Accidental Release Measures

- INDIVIDUAL NOTES :
- ** Immediately stop the leak of the liquid, remove the leaked liquid as soon as possible.
- ENVIRONMENTAL NOTES :
- ** Prevent pollution of water or soil.
- CLEAN PROCEDURES :
- ** Clean up small spill requires appropriate methods, such as use absorbent material to absorb or use motor extract.

7. Handling and Storage

♦ Handling:

- A. Don't do the container welding, heating or drilling and the lid should be closed. It's dangerous after the empty bucket sufficiently heated.
- B. When do the process of handling, keep the proper temperature and ventilation of the environment.
- C. Avoid with water, or cause the pollution of water.

♦ Storage:

- A. Store containers in a cool, dry, ventilated place, and keep them away from flame, sparks or other sources of ignition.
- B. The containers must be safely sealed clearly marked and avoid damage and collision.

8. Exposure Controls / Personal Protection

Engineering controls: There is no need ventilation, but use this item under a high pressure job in general; there is the special ventilation equipment.

Inhalation Protection: Wear respiratory masks.

Hands/Feet Protection: suitable and durable plastic or rubber gloves, wear securely footwear like rubber.

Eye Protection: Wear safely glasses with side shields, chemical goggles.

Skin & Body Protection: Any routine contact with used engine oil should require wearing protective clothing such as gloves, boots or apron made of neoprene, nitrile, etc. suitable for the application.

Hygiene:

- a. Keep good personal. Wash entirely with soap and water after handling product.
- b. Prohibit smoking and eating in working area.
- c. Clean affected clothing shoes, etc.
- d. Keep working areas clean.

9. Physical & Chemical Properties

Appearance & color: Light Amber liquid

Boiling point (deg. C) : 65° C

Vapor pr. (mmHg@ 25 deg. C) : 99.8 mm Hg

Density (kg/l at 15 deg. C) : 0.725 @20°C g/cm3

Vapor density (air = 1) : 1.1 pH: None Solubility (water) : Not available

Volatile Component (% vol.) : None Evaporation : None Flash point deg. C -6.6° C Viscosity(100 $^{\circ}$ C) : None

10. Stability & Reactivity

Chemical stability: The products are stable.

Conditions to avoid: Sparks or flame.

Materials to avoid: Acids, alkalis, strong oxidants and temperature

above the boiling point

Hazardous decomposition products : Carbon dioxide, carbon monoxide

11. Toxicological Information

Acute Effects:

Eyes & Skin: May irritate eyes

Skin: Not expected to have serious effects to skin if thoroughly

removed by washing with soap and water.

Swallow: May by harmful if swallowed.

Toxicity: No specific data.

12. Ecological Information

Environmental effects:

Chronic toxicity to fish, NOEC> 5000mg / L (seven) -IUCLID data

Chronic toxicity to water invertebrates, NOEC> 552mg / L (seven) -IUCLID data

Persistence and degradability: No specific data.

Bio accumulative: No specific data.

The mobility in soil: No specific data.

Other adverse effects: No specific data.

13. Disposal Considerations

Disposals are different from countries, or territories.

The user must operate according to the laws & rules in their country.

14. Transport Information

UN/ADR/RID/IMDG/IATA/ANDR/UK: Not regulated

Hazard Classification: 9

Packing type: Ⅲ

UN Shipments: UN 3082

Hazard identification: 9,EHSM

Product Name: Other Tube Material, Liquid, Not Specified (Content / Contents: Ethyl

2-Hexyl Nitrate)

Sea transport
IMDG
Hazard class:9
Packing group:III
ID number:UN 3082
Hazard label:9, EHSM
Marine pollutant:YES
Proper shipping name:
ENVIRONMENTALL <mark>Y HAZARDOU</mark> S
SUBSTANCE, LIQUID <mark>, N.O.S. (cont</mark> ains
2-ETHVI HEYVI NITRATE)

Air transport	
IATA/ICAO	9
Hazard class:	III and a second
Packing group:	UN 3082
ID number:	9, EHSM
Hazard label:	

Proper shipping name:

ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, LIQUID, N.O.S. (contains

2-ETHYLHEXYL NITRATE)

15. Regulatory Information

16. Other information

Issuer name: Ding Oil International Trading Company Ltd.

No.100-61, Fengren Rd., Fengshan Dist., Kaohsiung City 830, Taiwan

Tel: +886 7 7405126

Issued date: Apr. 20, 2017

Revision No.: 1

Label/other information: Not available.

^{*}Labor safety rules.

^{*}Road & traffic safety rules.

^{*}Taiwan industrial disposals treatment and storage operation regulations and facility standards.

Remarks to reader:

The information provided in this MSDS is from reliable source we trust. We do not guarantee any liability for consequences of the use this information since it may be used under condition out of our control or knowledge.

And it is also possible, that extra data could be made available after this MSDS was issued. All the material may present unknown hazards, the users should review this information and use with caution. The final determination of the suitability of any material is the sole responsibility of the user.

