MATERIAL SAFETY DATA SHEET



4T BMX 5W40 MB FULLY SYNTHETIC

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: 4T BMX 5W40 MB FULLY SYNTHETIC

Manufacturer Name: Ding Oil International Trading Co., Ltd

Address: 1F., No. 17, Ln. 31, Sec. 1, Jianguo Rd., Fengshan Dist., Kaohsiung City 830, Taiwan (R.O.C.)

Telephone Number: +886-7-788-0250

Emergency Telephone Number: +886-7-788-0250

Fax Number: +886-7-787-0209

II. HAZARDS IDENTIFICATION

NFPA Ratings (Scale 0-4): NFPA Fire=1

The Most Important Hazardous Effects:

- 1. Adverse Human Health Effects: (For Long Term Exposure)
 - Eye Contact: Irritation.
 - Skin Contact: May cause dermatitis.
 - Inhalation: Inhalation of oil mist or vapors at elevated temperature may cause respiratory irritation.
 - Ingestion: No information is available.
- 2. Environmental Effects: No information is available.
- 3. Physical and Chemical Hazards: Mist or vapors can produce at elevated temperatures.
- 4. Specific Hazards: No information on significant adverse effects.

Main Symptoms:

- > Eye Contact: Irritation.
- Skin Contact: No information is available.
- Inhalation: No information on significant adverse effects.
- Ingestion: No information is available.

III. COMPOSITION, INFORMATION ON INGREDIENT

Chemical Properties: Hydrocarbons

Ingredients	Concentration (%)	CAS No.	EINECS No.
Paraffinic Distillate	70.0% ~ 99.0%	64742-54-7	265-157-1
Engine oil additive	1.0% ~ 30.0%		
Zinc alkyl dithiophosphate	<1.69	68649-42-3	
Diphenylamine	<0.08	122-39-4	204-539-4

IV. FIRST AID MEASURES

Emergency Procedures:

- Inhalation: Remove personnel from exposure area to fresh air immediately. If breathing is difficult, give oxygen. If breathing ceases, use an oxygen rescuer or similar device to perform artificial respiration. Get medical attention immediately.
- Skin Contact: Remove contaminated clothing, jewelry and shoes immediately. Wash with soap or mild detergent and large amounts of water until no evidence of chemical remains (at least 15~20 minutes). If irritation or adverse symptoms develop, seek medical attention.
- Eye Contact: Flush eyes immediately with running water for at least fifteen minutes, occasionally lifting upper and lower lids, until no evidence of chemical remains. Get medical attention immediately.
- Digestion: If swallowed, do not induce vomiting. If conscious, give 1~2 water to drink. If vomiting occurs, keep head lower than hips to help prevent aspiration. Get medical attention immediately.

Protection of First-aider: No information is available.

Notes to Physician: No information is available.

V. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Regular dry chemical, carbon dioxide, water, and regular foam. Large fires: Use regular foam or flood with fine water spray.

Specific Hazards: Combustion conditions, oxides of the following elements will formed Carbon dioxide, water, sulfur, nitric oxide. Incomplete burning can produce carbon monoxide and other harmful products.

Special Fire Fighting Procedures:

- 1. Fire fighters should wear proper protective equipment stay upwind.
- 2. Move container from fire area and shut off source if it can be done without risk.
- 3. Cool containers with water spray until well after the fire is out.

- 4. Do not scatter spilled material with high-pressure water streams.
- 5. Keep unnecessary people away, isolate hazard area and deny entry.
- 6. Avoid inhalation of material or combustion by-products.

VI. ACCIDENTAL RELEASE MEASURE

Personal Precautions:

- 1. Avoid heat, flames, sparks and other sources of ignition.
- 2. Stop leak if possible without personal risk.
- 3. Reduce vapors with water spray.

Environmental Precautions:

- 1. Eliminate all open flame in vicinity of spill or released vapor.
- 2. Stop the source of the leak or release.
- 3. Clean up releases as soon as possible.
- 4. Contain liquid to prevent further contamination of soil, surface water or groundwater.

Methods for Cleaning Up:

- 1. Clean up small spills using sand or other non-combustible material.
- 2. Collect spilled material in appropriate container for disposal.
- 3. Where feasible and appropriate, remove contaminated soil.
- 4. Follow prescribed procedures for reporting and responding to larger releases.

VII. HANDLING AND STORAGE

Handling:

- 1. Wear protective equipment, if exposure conditions warrant.
- 2. Wash thoroughly after handling.
- 3. Use with adequate ventilation.
- 4. Handle in accordance with all current regulations and standards.

Storage:

- 1. Keep away from heat, sparks and flames.
- 2. Store in well-ventilated area.
- 3. Store in a tightly closed container.
- 4. Store in a cool, dry place.
- 5. Bond and ground during transfer.
- 6. Keep separated from incompatible substances.

7. Storage in accordance with all current regulations and standards.

VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Control:

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Control Parameter:

HAZARDO <mark>US</mark>	TWA	STEL	CEILING
MATERIAL			
Mineral Oil Mist	ACGIH: 5 mg/m ³	NIOSH: 10mg/m ³ UK	
	NIOSH: 5 mg/m ³	OES : 10mg/ <mark>m³</mark>	
A 1	OSHA: 5 mg/m ³		

Personal Protection Equipment:

- Respiratory Protection: Not generally required unless needed to prevent respiratory irritation. In case of spill or leak resulting in unknown concentration, use NOISH approved supplied air respirator.
- ➤ Hand Protection: Wear appropriate chemical resistant gloves.
- Eye Protection: Wear splash resistant safety goggle sur face shield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.
- Skin and Body Protection: Wear appropriate chemical resistant clothing. Remove any chemical soaked clothing immediately.

IX. PHYSICAL AND CHEMICAL PROPERTIES

Appearance & color:	Clear & L3.5	
Boiling point (deg. C):	Not Determined	
Vapor pr. (mmHg@ 25 deg. C) :	None	
Density (kg/l at 20 deg. C):	0.854@20°C g/cm ³	
Vapor density (air = 1) :	None	
pH:	None	
Solubility (water) :	Not available	
Volatile Component (% vol.) :	None	
Evaporation:	None	
Flash point deg. C	>228 ℃	
Viscosity(100°C):	15.38 cSt	
Pour point :	>-39℃	

X. STABILITY AND REACTIVITY

Stability: Stable at normal temperatures and pressure.

Possible Hazardous Reactions: Will not polymerize.

Conditions to Avoid: Avoid extreme heat. Avoid contact with incompatible material.

Materials to Avoid: Acid. Strong oxidizing agents.

Hazardous Decomposition Products: Oxides of carbon, various hydrocarbons.

XI. TOXICOLOGICAL INFORMATION

Acute Toxicity:

Inhalation: No data available.

Skin Contact: No data available.

Eye Contact: May irritate to eyes.

Ingestion: No data available.

Local Effect: No data available.

Sensitization: No data available.

Chronic Toxicity:

Inhalation: No data available.

Skin Contact: No data available.

Eye Contact: No data available.

Ingestion: No data available.

Specific Effects: No data available.

XII. ECOLOGICAL INFORMATION

Environmental Mobility: Fates:

This material is not expected to present any environmental problems other than those associated with oil spills.

XIII. DISPOSAL CONSIDERATIONS

Subject to disposal regulations: This product is a controlled waste. Dispose in accordance with all applicable regulations.

XIV. TRANSPORT INFORMATION

UN/ADR/RID/IMDG/IATA/ANDR/UK : Not regulated

XV. REGULATORY INFORMATION

Suitable Regulations:

- 1. All components comply with EINECS, TSCA, DSL, AICS, ECL and MITI.
- 2. EC dangerous substances/preparations classification: not regulated.

XVI. OTHER INFORMATION

Reference Literatures	1. OHS 15037
	2. OHS 50243
Made By	Ding Oil International Trading Co., Ltd.
Creation Date	Apr. 28, 2020

REMARKS TO READER:

- The information provided in this MSDS is from reliable source we trust. We do not guarantee any liability for consequences of the use this information since it may be used under condition out of our control or knowledge.
- And it is also possible, that extra data could be made available after this MSDS was issued. All the material may present unknown hazards, the users should review this information and use with caution. The final determination of the suitability of any material is the sole responsibility of the user.